

Reference - Farmall A vs Farmall C (large) - PLEASE 3-HOLE PUNCH



FARMALL® TRACTORS

FARMALL 95A/105A/115A VS. FARMALL 90C/100C/110C/120C

MODELS	FARMALL 95A/105A/115A	FARMALL 90C/100C/110C/120C
POWER		
Engine HP*	97 / 112 / 120	86 / 99 / 107 / 117
PTO HP*	78 / 92 / 100	73 / 85 / 93 / 100
PTO Speed (Standard / Optional)	540 / 540/540E or 540/1,000	540 / 540/1,000 120C = 540/1,000 / N/A
Engine Speed at PTO Speed - 540 / 540E / 1000	1,876 / 1,535 / 2,125	1,938 / N/A / 1,926
# of Cylinders	4	4
Displacement	207 in. ³ (3.4 L)	207 in. ³ (3.4 L)
Emission Level	Tier 4 B/Final	Tier 4 B/Final
Emission Components	CEGR, SCR	CEGR, SCR
Fuel Tank (Cab / Non-Cab)	29 gal. (110 L) / 24 gal. (91 L)	30.3 gal. (115 L) / 30.3 gal. (115 L)
TRANSMISSION		
Type (Standard / Optional)	12×12 power shuttle / N/A	12×12 power shuttle / 24×24 with Hi-Lo
Creep	Standard transmission is creeper ready	Optional with 12×12
MFD Engagement	Electro-hydraulic engagement	Electro-hydraulic engagement
HYDRAULICS		
Implement Pump	16.9 gpm (64.0 L)	16.9 gpm (64.0 L)
Steering Pump	9.7 gpm (36.7 L)	9.7 gpm (36.7 L)
Total Pump Flow	26.6 gpm (100.7 L)	26.6 gpm (100.7 L)
Rear Remotes (Standard / Optional)	2 / 3	2 / 3
3 POINT		
3 Point Lift Capacity @ 24" (Standard / Optional)	3,200 lb. (1,451 kg) / 7,716 lb. (3,500 kg)	4,339 lb. (1,968 kg) / 5,620 lb. (2,549 kg)
External Ground Controls	N/A	Optional
Lower Links	Telescopic	Telescopic
AXLES		
Front	2WD or MFD	2WD or MFD
Rear	Flange	Flange
LOADER (SEE LOADER SHEET FOR SPECIFICATIONS)		
Loader Model	L575	L620 or L630
Factory Installed	No	Yes
Third Function Diverter Valve	Optional	Optional
TIRES		
Bias	Various sizes available	Various sizes available
Radial	N/A	Various sizes available
Additional Options	Specialty & Poultry, various sizes available	Specialty, various sizes available
WEIGHTS AND DIMENSIONS		
Weight (Cab / Non-Cab)	8,492 lb. (3,860 kg) / 7,689 lb. (3,495 kg)	8,157 lb. (3,700 kg) / 7,474 lb. (3,390 kg)
Overall Length	161.6 in. (4,105 mm)	163 in. (4,144 mm)
Overall Height (Cab MFD)	106 in. (2,690 mm) with 16.9-34 tires	102 in. (2,591 mm) with 18.4-34 tires
Overall Height (Non-Cab MFD)	103 in. (2,615 mm) with 16.9-34 tires	106 in. (2,690 mm) with 18.4-34 tires
Wheelbase (Cab 2WD / Non-Cab 2WD)	91 in. (2,311 mm) / 85.6 in. (2,174 mm)	92.25 in. (2,343 mm) / 92.25 in. (2,343 mm)
Wheelbase (Cab MFD / Non-Cab MFD)	89 in. (2,261 mm) / 83.7 in. (2,126 mm)	90 in. (2,286 mm) / 90 in. (2,286 mm)
OPERATOR ENVIRONMENT		
Deck (Non-Cab)	Semi flat deck	Flat deck
Seat (Cab)	Standard air seat	Deluxe air seat with 15 degrees of swivel
Instructor's Seat	Standard	Optional
High Visibility Roof Panel	Standard	Optional
Radio (Standard / Optional)	Radio ready / Bluetooth® radio	Bluetooth radio / N/A
Poultry Configuration	Optional	N/A

* at 2,300 ERPM rated engine speed

— FOR INTERNAL USE ONLY —

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2020 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates.

Printed in U.S.A. www.caseih.com

CIH20070210 08/2020